

DuraFlood Spec

LED Flood Lights



DuraFlood Spec 300



DuraFlood Spec 150/200 Slipfitter



DuraFlood Spec 100 Yoke



DuraFlood Spec 30/50 Knuckle

- » **5 Year Warranty**
- » UL/DLC Listed
- » 30W, 50W, 100W, 150W, 200W and 300W options stocked in multiple mounting options
- » **480V Options** in stock
- » 5000K CCT
- » SMT 3030 LEDs with **Mean Well drivers**
- » Rugged die-cast aluminum housing, heatsink and tempered glass construction
- » Sealed and gasketed - **IP65 Wet Location Rating**
- » >50,000 Hour Lifespan

200W / 300W TECHNICAL SPECS

Part Number	DFS200S-BRZ-120D5K	DFS200Y-BRZ-120D5K	DFS200S-BRZ-120D5KA-4V	DFS300S-BRZ-90D5K	DFS300S-BRZ-90D5KA-4V
Power // Lumens	200W // 27,000	200W // 27,000	200W // 27,000	300W // 45,000	300W // 45,000
Mount	Slipfitter	Yoke	Slipfitter	Slipfitter	Slipfitter
Op Voltage	100 - 277 VAC	100 - 277 VAC	277-480 VAC	100 - 277 VAC	277-480 VAC
Replacement	750W MH			1000W MH	
Dimensions	15.1" x 10.8" x 4.5"			13" x 9" x 7"	
Weight	18.7 lbs			14.0 lbs	
EPA	1.4 ft ²			1.0 ft ²	

100W / 150W TECHNICAL SPECS

Part Number	DFS100S-BRZ-120D5K	DFS100Y-BRZ-120D5K	DFS150S-BRZ-120D5K	DFS150Y-BRZ-120D5K	DFS150S-BRZ-120D5KA-4V
Power // Lumens	100W // 13,000	100W // 13,000	150W // 20,250	150W // 20,250	150W // 20,250
Mount	Slipfitter	Yoke	Slipfitter	Yoke	Slipfitter
Op Voltage	100 - 277 VAC	100 - 277 VAC	100 - 277 VAC	100 - 277 VAC	277-480 VAC
Replacement	250 - 400W MH		400W MH		
Dimensions	12.5" x 9.0" x 3.7"		15.1" x 10.8" x 4.5"		
Weight	12.8 lbs		16.0 lbs		
EPA	1.0 ft ²		1.4 ft ²		

30W / 50W TECHNICAL SPECS

Part Number	DFS30K-BRZ-120D5K	DFS30Y-BRZ-120D5K	DFS50K-BRZ-120D5K	DFS50Y-BRZ-120D5K
Power // Lumens	30W // 3,300	30W // 3,300	50W // 6,000	50W // 6,000
Mount	Knuckle	Yoke	Knuckle	Yoke
Op Voltage	100 - 277 VAC	100 - 277 VAC	100 - 277 VAC	100 - 277 VAC
Replacement	150W Par 38		250W Par 38	
Dimensions	6.6" x 4.9" x 2.8"		9.4" x 6.3" x 3.1"	
Weight	3.5 lbs		5.7 lbs	
EPA	0.3 ft ²		0.5 ft ²	

OPTIONAL ACCESSORIES

GLARE-REDUCING HOODS



Part Number: DFSXXX-H

Optional glare-reducing hoods attach to the top and sides of the fixtures for increased precision and light distribution. To order replace X in part number with fixture wattage.

TRUNNION MOUNT



Part Number: DFS-T

Optional trunnion mount bolts to the bottom of the fixture in order to mount on a flat surface or overhang. Bolts in using supplied hardware. Not compatible with DFS30 and DFS50 fixtures.

PHOTOCELL



Part Number: DFS-PC

Dawn-to-dusk photocells automatically turn the fixture off when ambient light is present. Please allow 2-3 business days for custom installation. Not compatible with DFS30 and DFS50 fixtures.